

Centrifugal Fan


離心風機

Ø250




- 1 Motor**
Cage type capacitor structure external rotor motor
- 2 Impeller**
Black PA nylon one-time injection moulding
- 3 Allowable environment temperature and humidity range:(under unconcretionary condition)**
-40°C ~ +80°C (temperature) 0% ~ 95% (humidity)
- 4 Protection**
Motor Internal with automatic recovery thermal protector
- 5 Voltage endurance**
AC 1,800V , 1 min at 0.5mA, 50/60 Hz
- 6 Insulation Grade**
design according to IEC61858 Grade F,
- 7 Protection Grade**
IP44

- 1 電機:**
籠形電容式外轉子電機
- 2 葉輪:**
黑色PA 尼龍一次性注塑成型,
- 3 允許環境溫度和濕度範圍:(非凝結狀態)**
-40°C ~ +80°C (溫度) 0% ~ 95% (濕度)
- 4 保護:**
電機內部帶自動恢復熱保護器
- 5 絕緣耐壓:**
AC 1800V 0.5mA 50/60Hz下耐壓1分鐘
- 6 絕緣隔絕等級:**
按 IEC61858 F級設計
- 7 電機防護等級:**
IP 44



- Ⓐ Rotation direction of blades : CW seen from the front impellers
- Ⓑ Power Connection: UL3266-18 Lead wire
- Ⓒ Unit weight: 2.7kg

- Ⓐ 風扇旋向：從扇葉方向看為順時針
- Ⓑ 電源連接：UL3266-18 引線連接
- Ⓒ 單機重量：2.7kg



Parameters

Type 產品型號	Motor 電機	Rated Voltage 額定電壓 V	Frequency 周波數 Hz	current 電流 (A)	Power 功率 (W) ^{+10%} / _{-20%}	Speed 回轉速度 (min ⁻¹)	Max Air Flow 最大風量 CFM m ³ /h	Static Pressure 最大靜壓 (Pa)	Noise 噪音 (dB)	Curve 曲綫	Capacitor 電容 (μ F)
C2S-250.48D	M2S9203-AF	115	50	1.24	116	2650	738 1250	550	69	①	10.0/250
			60	1.35	150	2950	797 1350	580	71		
C2E-250.48D	M2E9203-AF	230	50	0.59	131	2650	738 1250	550	69	①	4.0/450
			60	0.76	173	2950	797 1350	580	71		
C2D-250.48D	M2D9203-AF	380	50	0.32	120	2650	738 1250	550	69	①	1.5/630
			60	0.46	172	2950	797 1350	580	71		