

HIGH LUMENS UFO TYPE LED HIGHBAY



Product Features

- Build with Anti-glare lens
- IP65 Weather-proof design
- Build-in Meanwell LED Driver
- Die-cast Aluminium construction
- High lumens efficiency - up to 150lm/W
- Made with LM-80 certified Philips LED chips
- Incl. removable hook and Australian standard plug



100W UFO TYPE LED HIGHBAY

Technical Specification

Model	UL-H100W
Product Code	04134100HBU
Watts	100W
LED Chips	196pcs Philips Luxeon 3030 LED
Driver	Meanwell HBG-100
Input Voltage	AC 100~277V
Power Factor	>0.95
Power Supply Efficiency	>95%
Beam Angle	60° / 90° / 120° Adjustable via diffuser
Colour Temp.	5500 - 6000K
CRI	Ra>80
Luminous Output	14000-14950lm
Size (excl. Hook)	Ø390*H230mm
Operating Temp.	-25 ~ +50°C
Operating Humidity	15~90%RH
Protection Grade	IP65 & IK08
Gross Weight	6.5 kg



120W UFO TYPE LED HIGHBAY

Technical Specification

Model	UL-H120W
Product Code	04134120HBU
Watts	120W
LED Chips	196pcs Philips Luxeon 3030 LED
Driver	Meanwell HBG-160
Input Voltage	AC 100~277V
Power Factor	>0.95
Power Supply Efficiency	>95%
Beam Angle	60° / 90° / 120° Adjustable via diffuser
Colour Temp.	5500 - 6000K
CRI	Ra>80
Luminous Output	16700-17150lm
Size (excl. Hook)	Ø390*H230mm
Operating Temp.	-25 ~ +50°C
Operating Humidity	15~90%RH
Protection Grade	IP65 & IK08
Gross Weight	6.5 kg



150W UFO TYPE LED HIGHBAY

Technical Specification

Model	UL-H150W
Product Code	04134150HBU
Watts	150W
LED Chips	196pcs Philips Luxeon 3030 LED
Driver	Meanwell HBG-160
Input Voltage	AC 100~277V
Power Factor	>0.95
Power Supply Efficiency	>95%
Beam Angle	60° / 90° / 120° Adjustable via diffuser
Colour Temp.	5500 - 6000K
CRI	Ra>80
Luminous Output	19000-20150lm
Size (excl. Hook)	Ø390*H230mm
Operating Temp.	-25 ~ +50°C
Operating Humidity	15~90%RH
Protection Grade	IP65 & IK08
Gross Weight	6.5 kg



200W UFO TYPE LED HIGHBAY

Technical Specification

Model	UL-H200W
Product Code	04134200HBU
Watts	200W
LED Chips	238pcs Philips Luxeon 3030 LED
Driver	Meanwell HBG-240
Input Voltage	AC 100~277V
Power Factor	>0.95
Power Supply Efficiency	>95%
Beam Angle	60° / 90° / 120° Adjustable via diffuser
Colour Temp.	5500 - 6000K
CRI	Ra>80
Luminous Output	23000-24150lm
Size (excl. Hook)	Ø390*H230mm
Operating Temp.	-25 ~ +50°C
Operating Humidity	15~90%RH
Protection Grade	IP65 & IK08
Gross Weight	6.5 kg

