



for

LED



BuLED

BuLED-50F-LG LED light accessory to replace MR16 fitting for LG Innotek modulars


Features VS Benefits

- * BuLED-50F LED light accessory includes one LED cooler and one LED housing to be assembled with LG Innotek modules to replace MR16.
- * Mechanical compatibility with direct mounting of the LED engines to the LED cooler and thermal performance matching the lumen packages.
- * For spotlight and downlight designs form 500 to 1800 lumen.
- * Thermal resistance range Rth 3.7°C/W.
- * Heatsink Diameter 48mm - Standard height 50mm , Other heights on request.
- * Housing Diameter 50mm - Standard height 50mm , Other heights on request.
- * Modular design with mounting holes foreseen for direct mounting of LG Innotek COB 10W/13W LED engines.
- * Forged from highly conductive aluminum.



Zhaga LED engine and radiator assembly is a unified future international standardization

- * Below you find an overview of LG Innotek LED modules which standard fit on the BuLED-30E series.
- * In this way mechanical after work and related costs can be avoided, and lighting designers can standardize their designs on a limited number of Star LED Heat Sinks.



LG Innotek LED engines Mounting Options

10W COB:

- LEMWM18580GGxxxx;
- LEMWM18580HGxxxx;
- LEMWM18580JGxxxx;
- LEMWM18580LGxxxx;
- LEMWM18580MGxxxx;

Green indicator marks.
Direct mounting with machine screws M2x6.5mm;

13W COB:

- LEMWM18680HGxxxx;
- LEMWM18680JGxxxx;
- LEMWM18680LGxxxx;
- LEMWM18680MGxxxx;

Green indicator marks.
Direct mounting with machine screws M2x6.5mm;



BuLED

BuLED-50F-LG LED light accessory to replace MR16 fitting for LG Innotek modulars

Mounting Options and Drawings & Dimensions

Example: BuLED-50F-LG-B-1

Example: BuLED-50F-LG-**1**-**2**


- 1** Anodising Color
 - B-Black
 - C-Clear
 - Z-Custom

- 2** Mounting Options - see graphics for details Combinations available
 - Ex.order code - 12
 - means option 1 and 2 combined


Notes:

- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MingfaTech.
- MingfaTech reserves the right to change products or specifications without prior notice.

MOUNTING OPTION	Module type	Holder NO.	THREA D	THREAD DEPTH	THREAD HOLE DISTANCE
1	COB 10W/13W	/	M2	6.5mm	22.0mm/ @180°



The thermal data table

	 BuLED
Model No.	BuLED-50F-LG
Heatsink Size	Φ48xH50mm
Housing Size	Φ50xH50mm
Material (Heatsink + Housing)	AL1070 + AL6063-T5
Finish	Black Anodized
Weight(g)	93.0
Thermal Wattage	15.0W
HeatsinkOs-a²	23458
Thermal Resistance	3.7

Pd = Pe x (1-ηL)	Heat sink to ambient thermal resistance Rhs-amb (°C/W)	Heat sink to ambient temperature rise Ths-amb (°C)
	BuLED-50F-LG	BuLED-50F-LG
2.5	5.6	14.0
4.5	5.3	24.0
7.0	4.6	32.0
9.5	4.3	41.0
12.0	4.1	49.0
15.0	3.7	55.0

