



for

LED



BuLED

BuLED-30E-LUM LED light accessory to replace MR16 fitting for Lumileds modulars


Features VS Benefits

- * BuLED-30E LED light accessory includes one LED cooler and one LED housing to be assembled with Lumileds modules to replace MR16.
- * Mechanical compatibility with direct mounting of the LED engines to the LED cooler and thermal performance matching the lumen packages.
- * For spotlight and downlight designs from 400 to 1200 lumen.
- * Thermal resistance range Rth 4.2°C/W.
- * Heatsink Diameter 48mm - Standard height 30mm , Other heights on request.
- * Housing Diameter 50mm - Standard height 50mm , Other heights on request.
- * Modular design with mounting holes foreseen for direct mounting of LUMILEDS Luxeon K and LueonCOB engines.
- * Extruded from highly conductive aluminum.



Zhaga LED engine and radiator assembly is a unified future international standardization

- * Below you find an overview of Lumileds LED modules which standard fit on the BuLED-30E series.
- * In this way mechanical after work and related costs can be avoided, and lighting designers can standardize their designs on a limited number of Star LED Heat Sinks.



LUMILEDS LED Modules directly Mounting Options

For the Luxeon K 3-UP/4-UP LED engines.

- LXK8-PWxx-0403;
- LXK8-PWxx-0004;
- LXK9-PWxx-0004;

Direct mounting with machine screws M3x8mm;
Blue indicator marks.

For the Luxeon K 6-UP/8-UP LED engines.

- LXK8-PWxx-0206;
- LXK8-PWxx-0008;

Direct mounting with machine screws M3x8mm;
Yellow indicator marks.

For the LuxeonCOB LED engines.

- LHC1-xxxx-1202;
- LHC1-xxxx-1203;

Direct mounting with machine screws M3x8mm;
Red indicator marks.



Mounting Options and Drawings & Dimensions

Example: BuLED-30E-LUM-B-1,2

Example: BuLED-30E-LUM-**1** - **2**

1 Anodising Color

- B-Black
- C-Clear
- Z-Custom

2 Mounting Options - see graphics for details Combinations available


Ex.order code - 12 means option 1 and 2 combined

Notes:

- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MingfaTech.
- MingfaTech reserves the right to change products or specifications without prior notice.



MOUNTING OPTION	Module type	Holder NO.	THREAD	THREAD DEPTH	THREAD HOLE DISTANCE
1	Luxeon K 3-UP Luxeon K 4-UP	/	M3	6.5mm	17.0mm/ @180°
2	Luxeon K 6-UP Luxeon K 8-UP	/	M3	6.5mm	21.7mm/ @180°
3	LuxeonCOB1202 LuxeonCOB1203	/	M3	6.5mm	24.5mm/ @180°



for

LED

BuLED

BuLED-30E-LUM LED light accessory to replace MR16 fitting for Lumileds modulars

The thermal data table

	
	<i>BuLED</i>
Model No.	BuLED-30E-LUM
Heatsink Size	Φ48xH30mm
Housing Size	Φ50xH50mm
Material	AL6063-T5
Finish	Black Anodized
Weight(g)	110.0
Thermal Wattage	12.0W
HeatsinkOs-a²	22820
Thermal Resistance (°C/W)²	4.2

	Pd = Pe x (1-ηL)	Heat sink to ambient thermal resistance Rhs-amb (°C/W)	Heat sink to ambient temperature rise Ths-amb (°C)
		BuLED-30E-LUM	BuLED-30E-LUM
Dissipated Power Pd(W)	2.5	6.2	15.5
	4.5	5.8	26.1
	7.0	5.2	36.4
	9.5	4.8	45.6
	12.0	4.2	50.4

