



EtraLED

EtraLED -OSR-9620 for OSRAM Modular Passive LED Cooler Φ 96mm


Features VS Benefits

- * The EtraLED -OSR-9620 OSRAM Modular Passive LED Coolers are specifically designed for luminaires using the OSRAM LED engines.
- * Mechanical compatibility with direct mounting of the LED engines to the LED cooler and thermal performance matching the lumen packages.
- * For spotlight and downlight designs from 800 to 3000 lumen.
- * Thermal resistance range Rth 1.8°C/W.
- * Modular design with mounting holes foreseen for direct mounting of OSRAM PrevaLED Core , SOLERIQ P and SOLERIQ S LED engines.
- * Diameter 96mm - standard height 20mm Other heights on request.
- * Extruded from highly conductive aluminum.



Zhaga LED engine and radiator assembly is a unified future international standardization

- * Below you find an overview of OSRAM engines COB's and LED modules which standard fit on the EtraLED coolers.
- * In this way mechanical after work and related costs can be avoided, and lighting designers can standardize their designs on a limited number of LED coolers.



OSRAM LED engines Mounting Options

Osram PrevaLED Core AC LED modules.

- | | |
|-----------------------|---------------------|
| PL-CORE AC -2000-827; | LEP -2000-827-C-AC; |
| PL-CORE AC -2000-830; | LEP -2000-830-C-AC; |
| PL-CORE AC -2000-840; | LEP -2000-840-C-AC; |

Osram PrevaLED Core Z3 LED modules.

- | | |
|-----------------------|-----------------------|
| PL-CORE -2000-830-Z3; | PL-CORE -3000-830-Z3; |
| PL-CORE -2000-840-Z3; | PL-CORE -3000-840-Z3; |
| PL-CORE -2000-930-Z3; | |

Osram PrevaLED Core Z4 LED modules.

- | | |
|-----------------------|-----------------------|
| PL-CORE-Z4 -2000-827; | PL-CORE-Z4 -3000-827; |
| PL-CORE-Z4 -2000-830; | PL-CORE-Z4 -3000-830; |
| PL-CORE-Z4 -2000-835; | PL-CORE-Z4 -3000-835; |
| PL-CORE-Z4 -2000-840; | PL-CORE-Z4 -3000-840; |
| PL-CORE-Z4 -2000-930; | |

Osram SOLERIQ S19 LED modules.

- | | |
|-------------------------|-------------------------|
| GW KAHJB1.EM-SSSU-27S3; | GW KAHJB1.EM-SQSS-27S3; |
| GW KAHJB1.EM-SSSU-30S3; | GW KAHJB1.EM-SQSS-30S3; |
| GW KAHJB1.EM-STTP-35S3; | GW KAHJB1.EM-SRST-35S3; |
| GW KAHJB1.EM-STTP-40S3; | GW KAHJB1.EM-SRST-40S3; |

Zhaga Book3 Gree indicator marks:

- BJB holder:47.319.2196.50 ;
 AAG.STUCCHI holder:8503-G2
 Direct mounting with machine screws M3x6mm;

Osram SOLERIQ P9 modules.

- | | |
|-------------------------|-------------------------|
| GW MAFJB1.EM-RTSQ-27S3; | GW MAFJB1.CM-RSSP-27S3; |
| GW MAFJB1.EM-RUSR-30S3; | GW MAFJB1.CM-RTSQ-30S3; |
| GW MAFJB1.EM-RUSS-35S3; | GW MAFJB1.CM-RTSR-35S3; |
| GW MAFJB1.EM-SPST-40S3; | GW MAFJB1.CM-RUSS-40S3; |
| GW MAFJB1.EM-SPST-50S3; | |

Zhaga Book11 Red indicator marks:

- BJB holder:47.319.6200.50
 AAG.STUCCHI holder:8501-G2
 Direct mounting with machine screws M3x6mm;

Tel:+86-769-39023131
 E-fax:+86-(020)28819702 ext:22122
 Email:sales@mingfatech.com
 Http://www.heatsinkled.com
 Http://www.mingfatech.com





for

LED



EtraLED

EtraLED -OSR-9620 for OSRAM Modular Passive LED Cooler Ø96mm

Mounting Options and Drawings & Dimensions

Example:EtraLED-OSR-9620-B-3

Example:EtraLED-OSR-96 **1** - **2** - **3**

1 Height (mm)

2 Anodising Color

B-Black

C-Clear

Z-Custom

3 Mounting Options - see graphics for details Combinations available

Ex.order code - 12

means option 1 and 2 combined


Notes:

- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MingfaTech.
- MingfaTech reserves the right to change products or specifications without prior notice.



STUCCHI
ideas are made of light

MOUNTING OPTION	Module type	Holder NO.	THREAD	THREAD DEPTH	THREAD HOLE DISTANCE
1	SOLERIQ P9	AAG.STUCCHI:8501-G2	M3	6mm	25.0mm/ 2-@120°
		BJB:47.319.6200.50			
2	PrevaLED Core AC	/	M3	6mm	35.0mm/ 2-@120°
	PrevaLED Core Z3				
	PrevaLED Core Z4				
	SOLERIQ S19				
		AAG.STUCCHI:8503-G2			
		BJB: 47.319.2196.50			



Tel:+86-769-39023131
 E-fax:+86-(020)28819702 ext:22122
 Email:sales@mingfatech.com
 Http://www.heatsinkled.com
 Http://www.mingfatech.com




for

LED

EtraLED

EtraLED -OSR-9620 for OSRAM Modular Passive LED Cooler Φ96mm

The thermal data table

	 <i>EtraLED-9620</i>
Model No.	EtraLED-OSR-9620
Size	Φ96xH20mm
Material	AL6063-T5
Finish	Black Anodized
Weight(gr)	144.0
Thermal Wattage	28.0W
HeatsinkOs-a²	50647
Heat Sink T Rise Above Ambient	1.80

Dissipated Power Pd(W)	Pd = Pe x (1-ηL)	Heat sink to ambient thermal resistance Rhs-amb (°C/W)	Heat sink to ambient temperature rise Ths-amb (°C)
		EtraLED-OSR-9620	EtraLED-OSR-9620
6		2.0	12
12		2.1	25
18		1.9	35
24		1.8	43
30		1.7	51

