



for

LED



*GooLED*

**GooLED-VOS-8665 Pin Fin LED Heat Sink  $\Phi$ 86.5mm for Vossloh-Schwabe**


**Features VS Benefits**

- \* The GooLED-VOS-8665 Vossloh-Schwabe Pin Fin LED Heat Sinks are specifically designed for luminaires using the Vossloh-Schwabe LED engines.
- \* Mechanical compatibility with direct mounting of the LED engines to the LED cooler and thermal performance matching the lumen packages.
- \* For spotlight and downlight designs from 1,800 to 5,200 lumen.
- \* Thermal resistance range Rth 1.56°C/W.
- \* Modular design with mounting holes foreseen for direct mounting of Vossloh-Schwabe COB series.
- \* Diameter 86.5mm - standard height 65.0mm Other heights on request.
- \* Forged from highly conductive aluminum.



**Zhaga LED engine and radiator assembly is a unified future international standardization**

- \* Below you find an overview of Vossloh-Schwabe COB's and LED modules which standard fit on the Pin Fin LED Heat Sinks.
- \* In this way mechanical after work and related costs can be avoided, and lighting designers can standardize their designs on a limited number of LED Pin Fin LED Heat Sink.



**Vossloh-Schwabe LED Modules directly Mounting Options**

Vossloh-Schwabe LUGA Shop Gen. 5/ Gen.6 COB Series (28.0\*28.0):

- |             |             |
|-------------|-------------|
| DMS120***G; | DMS120***H; |
| DMS12C***G; | DMS12C***H; |
| DMS18C***G; | DMS18B***H; |
| DMS18Q***G; |             |

Vossloh-Schwabe LUGA Shop TW COB Series:

- TW2817;  
TW2820;
- With the Zhaga Book 3 holders for the green indicator marks.  
BJB holder: 47.319.2030.50;  
AAG.STUCCHI: 8102-G2
- Without the holders for the blue indicator marks.  
Direct mounting with machine screws M3x6.5mm.

Vossloh-Schwabe LUGA Shop Gen. 5/ Gen.6 COB Series (19.0\*19.0):

- |             |             |
|-------------|-------------|
| DMS124***G; | DMS125***H; |
| DMS125***G; | DMS126***H; |
| DMS126***G; | DMS128***H; |
| DMS128***G; |             |

- With the Zhaga Book 3 holders for the green indicator marks.  
BJB holder: 47.319.2021.50;  
AAG.STUCCHI: 8101-G2
- Without the holders for the red indicator marks.  
Direct mounting with machine screws M3x6.5mm.



Mounting Options and Drawings & Dimensions

Example:GooLED-VOS-8665-B-1,2

Example:GooLED-VOS-86 **1** - **2** - **3**

**1** Height (mm)

**2** Anodising Color

B-Black

C-Clear

Z-Custom

**3** Mounting Options - see graphics for details Combinations available


Ex.order code - 12

means option 1 and 2 combined

Notes:

- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MingfaTech.
- MingfaTech reserves the right to change products or specifications without prior notice.

MOUNTING OPTION	Module type	Holder NO.	THREAD	THREAD DEPTH	THREAD HOLE DISTANCE
1	COB series (19.0*19.0)	/	M3	6.5mm	26.8mm/ 2-@180°
2	COB series (28.0*28.0)	/	M3	6.5mm	32.2mm/ 2-@180°
3	COB series (28.0*28.0)	BJB Holder 47.319.2030.50	M3	6.5mm	35.0mm/ 2-@180° (Zhaga book 3)
		AAG.STUCCHI 8102-G2			
	COB series (19.0*19.0)	BJB Holder 47.319.2021.50			
		AAG.STUCCHI 8101-G2			



## GooLED

### GooLED-VOS-8665 Pin Fin LED Heat Sink $\Phi 86.5\text{mm}$ for Vossloh-Schwabe

#### The product data table

	<b>Model No.</b>	GooLED-VOS-8665
	<b>Heatsink Size</b>	$\Phi 86.5 \times H65\text{mm}$
	<b>Heatsink Material</b>	AL1070
	<b>Finish</b>	Black Anodized
	<b>Weight (g)</b>	293.0
	<b>Dissipated power (T<sub>hs-amb</sub>,50°C)</b>	32.0 (W)
	<b>Cooling surface area (mm<sup>2</sup>)</b>	95583
	<b>Thermal Resistance (R<sub>hs-amb</sub>)</b>	1.56 (°C/W)


#### The thermal data table

\* Please be aware the dissipated power Pd is not the same as the electrical power Pe of a LED module.

\* To calculate the dissipated power please use the following formula:  $P_d = P_e \times (1 - \eta_L)$ .

Pd - Dissipated power ; Pe - Electrical power ;  $\eta_L$  = Light efficiency of the LED module;


Dissipated Power Pd(W)	Pd = Pe x (1- $\eta_L$ )	Heat sink to ambient thermal resistance R <sub>hs-amb</sub> (°C/W)	Heat sink to ambient temperature rise T <sub>hs-amb</sub> (°C)
		GooLED-VOS-8665	
8.0		2.75	22.0
16.0		2.13	34.0
24.0		1.75	42.0
32.0		1.56	50.0
40.0		1.45	58.0



\*The aluminum substrate side of the package outer shell is thermally connected to the heat sink via TIM (Thermal interface material).

MingFa recommends the use of a high thermal conductive interface between the LED module and the LED cooler.

Either thermal grease, A thermal pad or a phase change thermal pad thickness 0.1-0.15mm is recommended.



\*Thermal resistance is a heat property and a measurement of a temperature difference by which an object or material resists a heat flow.

Geometric shapes are different, the thermal resistance is different. Formula:  $\theta = (T_{\text{hs}} - T_{\text{a}}) / P_d$

$\theta$  - Thermal Resistance [°C/W] ;  $T_{\text{hs}}$  - Heatsink temperature ;  $T_{\text{a}}$  - Ambient temperature ;

\*The thermal resistance between the junction section of the light-emitting diode and the aluminum substrate side of the package outer shell is  $R_{\text{junction-case}}$ , the thermal resistance of the TIM outside the package is  $R_{\text{interface (TIM)}}$  [°C/W], the thermal resistance with the heat sink is  $R_{\text{heatsink-ambient}}$  [°C/W], and the ambient temperature is  $T_{\text{ambient}}$  [°C].

\*Thermal resistances outside the package  $R_{\text{interface (TIM)}}$  and  $R_{\text{heatsink-ambient}}$  can be integrated into the thermal resistance  $R_{\text{case-ambient}}$  at this point. Thus, the following formula is also used:

$$T_{\text{junction}} = (R_{\text{junction-case}} + R_{\text{case-ambient}}) \cdot P_d + T_{\text{ambient}}$$