

HibayLED

HibayLED-21088 Modular Fastening LED Heat Sinks (Passive) Φ 210mm

Features VS Benefits




- *The HibayLED-21088 Modular Fastening LED Heat Sinks (Passive) are specifically designed for luminaires using the PBC modules engines.
- * Modular design with mounting holes foreseen for direct mounting of PCB modules.
- * For Highbay designs from 8000 to 11000 lumen.
- * Thermal resistance range R_{th} 0.52°C/W.
- * Modular design with mounting holes foreseen for direct mounting of 5630-8C22B and 5730-5C16B..... series chips.
- * Diameter 210.0mm - standard height 88.0mm.




Unique Advantages

- * The volume and weigh reduce more than 30% than extrusion heatsinks;
- * No limited of life cycle;
- * This type compatible for PCB/SMT type modules;
- * Compatible for MingWell HBG type drive
- * All aluminium.

Suitable for the following PCB type modules




Product drawing



HibayLED

HibayLED-21088 Modular Fastening LED Heat Sinks (Passive) Φ 210mm

The thermal data table

	 <p><i>HibayLED</i></p>
Model No.	HibayLED-21088
Size	Φ 210.0xH88.0mm
Material	AL 1070
Finish	Clear anodized
Weight(gr)	1060.0
Thermal Wattage	100.0 W
Heatsink Θ s-a ²	773029
Heat Sink T Rise Above Ambient	0.52

Heat sink to ambient temperature rise $T_{hs-amb}(^{\circ}C)$ $t_a=25^{\circ}C$

