

BULED

XSA-391 LED light accessory to replace MR16 fittings by Xicato XTM

Features VS Benefits

- *XSA-391 LED light accessory includes one LED cooler and one LED housing to be assembled with Xicato XTM LED modules to replace MR16.
- * Mechanical compatibility with direct mounting of the LED modules to the LED cooler and thermal performance matching the lumen packages.
- * Thermal resistance range Rth 3.7°C/W.
- * Xicato Thermal Class E , (60° tilt angle, 40°C ambient) .
- * The cooler design with mounting holes foreseen for direct mounting of Xicato XTM Module .
- * Heatsink Diameter 48mm - Standard height 50mm , Other heights on request.
- * Housing Diameter 50mm - Standard height 50mm , Other heights on request.
- * Extruded from highly conductive aluminum.



*The XSA-391 LED light accessory Xicato Star Heat Sink is standard foreseen from a variety of mounting holes which allow direct mounting of all Xicato Spot and down light LED modules and secondary optics on the LED heat sink.

*In this way mechanical afterwork and related costs can be avoided, and lighting designers can standardize their designs on a limited number of LED coolers.



*Below you find an overview of Xicato LED modules which standard fit on the XSA-391 LED light accessory .

*MingFa performs thermal validation tests on each of the LED modules mounted on the LED cooler and publishes.

*This data in the Xicato Cooler thermal validation reports.

*For a full overview of available LED coolers for Xicato LEDs, please refer to the Xicato LED cooler overview on.

XICATO



XSA-391 LED light accessory ,Heatsink standard height 50mm for Xicato LED modules Mounting Options

Xicato XTM LED modules with Shinland Zhaga holder.

XTM19-8027-xxx ; XTM19-8040-xxx ;
 XTM19-8030-xxx ; XTM19-V830-xxx ;
 XTM19-8035-xxx ;

Direct mounting by Zhaga mounting holes with 2 screws M3 x 8mm; with Shinland Zhaga holder.
 Blue indicator marks.

BULED

XSA-391 LED light accessory to replace MR16 fittings by Xicato XTM

Mounting Options and Drawings & Dimensions

Example: XSA-391-M3-B-2

Example: XSA-391-M3 - **1** - **2**

- 1** Anodising Color
 - B-Black
 - C-Clear
 - Z-Custom

- 2** Mounting Options - see graphics for details Combinations available
 - Ex.order code - 12
 - means option 1 and 2 combined





MOUNTING OPTION	PART NUMBER	THREAD	THREAD DEPTH
NONE	XSA-391-M3-B-N	NONE	NONE
1	XSA-391-M3-B-1	M3*0.5	6mm



MingFa recommends the use of a high Thermal conductive interface between the LED Module and the LED cooler. Either thermal grease, A thermal pad or a phase change thermal pad Thickness 0.1-0.15mm is recommended.

XTM MOUNTING OPTION M3:
2X DRILL & TAP M3X0.5,
6mm DEEP MIN

0.05
(INSIDE THE DIAMETER
INDICATED, MODULE
SIDE ONLY)



MOUNTING OPTIONS 1
(2x) M3*0.5 6mm @180°



Notes:

- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MingfaTech.
- MingfaTech reserves the right to change products or specifications without prior notice.

BuLED

XSA-391 LED light accessory to replace MR16 fittings by Xicato XTM

The thermal data table

	
	BuLED
Model No.	XSA-391
Heatsink Size	Φ48xH50mm
Housing Size	Φ50xH50mm
Material	AL6063-T5
Finish	Black Anodized
Weight(g)	160
Thermal Wattage	15W
HeatsinkOs-a²	36868
Thermal Resistance (°C/W)²	3.7

Dissipated Power Pd(W)	Pd = Pe x (1-ηL)	Heat sink to ambient thermal resistance Rhs-amb (°C/W)	Heat sink to ambient temperature rise Ths-amb (°C)
		XSA-391	XSA-391
2.5W		5.6	14
4.5W		5.3	24
7.0W		4.6	32
9.5W		4.3	41
12W		4.1	49
15W		3.7	55

