

KEUNDO

SUPRAFX 1800

Wide Format Color Fixation



SUPRAFX 1800 SPECIFICATIONS

MATERIAL TYPE	Pre-coated Dye-Sublimation Polyester, Mesh polyester and etc.
FIXATION SPEED	40 ~ 60m/hr (Normal), & depends on the material.
FIXATION WIDTH	Available up to 1,800mm
FIXATION METHOD	Roll to Roll and Combined to use a same roll with SupraQ 3200-TX.
FEEDING SYSTEM	Automated intelligent feeding of media supply system. Applied mechanical control tension to generate constant tension of material(s).
POWER	220V AC Single Phase 35Amp
DIMENSION & WEIGHT	2,850(w) x 1,050(d) x 1,100(h) (Unit : mm) / 500kg

KEUNDO

SUPRAFX 3200

Grando Format Color Fixation



SUPRAFX 3200 SPECIFICATIONS

MATERIAL TYPE	Pre-coated Dye-Sublimation Polyester, Mesh polyester and etc.
FIXATION SPEED	80 ~ 120m/hr
FIXATION WIDTH	Available up to 3,200mm
FIXATION METHOD	Roll to Roll and Combined to use a same roll with SupraQ 3200-TX.
FEEDING SYSTEM	Automated intelligent feeding of media supply system. Applied mechanical control tension to generate constant tension of material(s).
POWER	AC 380V 3phase 35KW
DIMENSION & WEIGHT	4,320(w) x 1,215(d) x 1,142(h) (Unit : mm) / 900kg



SCG DIGITAL AMERICA INC.

Address: 13300 Brooks Dr. #D Baldwin Park, CA91706

Phone: (626)223-4492 / (626)552-5075

Website: www.scg-america.com Email: marketing@scg-america.com