

DVB T2+S2 HD Combo Quotation sheet(Complete unit)

Highlight: Support WIFI/3G/IKS/CCAM/POWERVU/YOUTUBE

Product Type				Packing Detail		
Model Number	STB-HP2202 T2+S2			UNIT	GIFT BOX	EXP CARTON
Solution	GX			Length (MM)	220	580
FOB Price(US\$)				Width (MM)	138	275
MOQ(PCS)				Height (MM)	40	210
Shipping terms	FOB SHENZHEN			Weight (KG)	0.7	9
Payment terms	30% deposit, balance before shipment			Volume (CBM)	N/A	
				Units per Carton	10PCS / Master carton	
Remarks of Price				Container Loading		
USD20/pc FOB Chengdu				Quantity/ 20' dry	8359CS	
				Quantity / 40 dry	14330 pcs	
				Quantity/ 40 HC	17310 pcs	
				Accessory		
				Remote Control, Battery,users manual,AV cable(1M)		

Front & Real Picture shoot



Main Feature	Powerful Multimedia Features
Chipset:GX	Photo: JPEG,BMP,PNG
Memory:512Mb	Audio: MP3、 AAC (.mp3、 m4a)
Flash:64Mb	Video: MPEG1、 MPEG2、 MPEG4、 H264、
DVB-T/T2, compliane with EN 300 744 DVB-T and EN 302 755 DVB-T2	Motion JPEG (avi.mpg、 .dat、 .vob、 .div、 .mov、 .mkv、 .mjpeg、 .ts、 .trp)
DVB-S/S2, compliane with EN 300 421 DVB-S and EN 302 307 DVB-S2	NTFS、 FAT32、 FAT16
QPSK, 8PSK, 16APSK and 32APSK	Jpeg/Audio combo playback
QPSK/8PSK 1 ~ 45Msps, 16APSK: 1 ~ 39Msps and 32APSK 1 ~ 32Msps	
Channel BW 1.7, 5, 6, 7, 8 MHz	Demodulation:
T2-Base profile o T2-Lite profile o Single and Multiple PLPs	QPSK, 16-QAM, 64-QAM, 256-QAM
Low IF (4.57 ~ 10MHz)	FEC: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6
Carrier acquisition range: ±650 kHz @ 8 MHz BW	Guard Interval: 1/128, 1/32, 1/16, 19/256, 1/8, 19/128, 1/4
Video decoder: MPEG-4/H.264 MP and HP, MPEG-2 MP@ML and MP@HL	FFT Mode:1K, 2K, 4K, 8K, 8KE, 16K, 16KE,32K, 32KE
Audio decoder: MPEG-1/2/4,AAC/HE-AAC/AC3,	
Tuner	Demultiplexer
IF input frequency: VHF: 174MHz - 230MHz/UHF: 474MHz - 860MHz	Standard ISO/IEC 13818-1; ARIB STB-B10
Bandwith: 6/7/8MHz	Input max. bit stream rate: 120Mbps (serial)/15MBps (parallel)
Input level: -83dBm	
Signal input: IEC-type female	Hardware
	Metal housing in black color
Decoding	LED display/7buttons
Mpeg transport stream and A/V decoding	USB: ONE USB2.0
Video standard: MPEG-4 AVC/H.264 HP@L4	ANT IN,LNB IN/USB/HD OUT/AV6,POWER ON/OFF
Aspect ratio: 4:3, 16:9	
Video resolution: 576i, 576p, 720p,1080i and 1080p	
Audio standard: ISO/IEC 14.496-3, AAC,	
Audio mode: mono, dual-channel, stereo	