

KOYAMA® Commercial /Truck Batteries

Keep your heavy-duty equipment operating with **KOYAMA** Commercial Batteries



Keep Heavy-Duty Equipment Running at top performance

Demanding commercial equipment requires nothing less than the most powerful, reliable batteries. This complete line of the toughest commercial product is specially engineered for durability while meeting high power ratings for heavy-duty engines.

Key Features and Benefits of the KOYAMA Commercial Line

- * Genuine calcium lead alloy provides longer waterless operation and extended battery life.
- * Anchor-locked elements with full-frame grids and tight-packed commercial plates resist the damaging effects of vibration, delivering more power-per-pound than other batteries.
- * Most of our commercial batteries contain premium "deep pocket" envelope separators, which protect the plates on all four sides to dramatically reduce shorting and extend service life.
- * Special computer-aided design and manufacturing means more durability for heavy-duty line-haul trucks, buses, farm tractors and off-road equipment.



KOYAMA® Commercial /Truck Batteries

HEAVY DUTY TRUCK BATTERY FOR COMMERCIAL VEHICLES												
Gr.No	Type No.	ETN NO.	Capacity	CCA	Dimension (mm)				Layout	Terminal	Weight	
		Old JIS NO.	(AH-20Hr)	(EN/SAE)	L	W	H	TH			KG	
12-VOLT HEAVY DUTY COMMERCIAL CONVENTIONAL BATTERIES												
EN	EN	61017	610 017 060	110	600	512	186	195	216	3	A	17.6
		62034	620 034 068	120	680	512	186	195	216	3	A	18.4
		63530	635 030 068	135	680	512	186	195	216	3	A	19.5
		63531	635 031 068	135	680	512	186	195	216	4	A	19.5
		64020	640 020 068	140	680	512	186	195	216	3	A	20.5
	B	64317	643 017 085	143	850	512	220	195	216	3	A	21.3
		65017	650 017 085	150	850	512	220	195	216	3	A	21.3
		66514	665 014 095	165	950	512	220	195	216	3	A	22.4
		67043	670 043 100	170	1000	512	220	195	216	3	A	23.5
		68032	680 032 100	180	1000	512	220	195	216	3	A	25.1
	C	70027	700 027 105	200	1050	512	275	215	236	3	A	27.3
		70029	700 029 105	200	1050	512	275	215	236	4	A	27.3
		71014	710 014 115	210	1150	512	275	215	236	3	A	29.3
		73011	730 011 120	230	1200	512	275	215	236	3	A	32.3
	D	60527	605 027 068	105	600	362	172	214	236	1	A	15.2
		60528	605 028 068	105	600	362	172	214	236	0	A	15.2
JIS	F51	115F51	N120	120	640	506	182	210	230	4	A	17.6
		150F51	N135	135	720	506	182	210	230	4	A	18.4
		145F51	N140	140	780	506	182	210	230	4	A	19.5
	G51	145G51	N150	150	950	506	220	210	230	4	A	20.3
		165G51	N160	160	950	506	220	210	230	4	A	21.3
		180G51	N170	170	950	506	220	210	230	4	A	22.4
		195G51	N180	180	1000	506	220	210	230	4	A	23.5
	H52	210H52	N200	200	1200	519	277	218	240	4	A	27.3
		245H52	N220	220	1300	519	277	218	240	4	A	29
BCI	4D	4D-950		150	950	528	214	224	246	4	A	20.3
	8D	8D-1300		200	1300	528	277	224	246	4	A	29
12-VOLT HEAVY DUTY COMMERCIAL SEALED BATTERIES												
EN	EN	61017	610 017 060	110	600	507	186	203	224	3	A	29.5
		62034	620 034 068	120	680	507	186	203	224	3	A	30.5
		63530	635 030 068	135	680	507	186	203	224	3	A	31.5
		63531	635 031 068	135	680	507	186	203	224	4	A	31.5
		64020	640 020 068	140	680	507	186	203	224	3	A	33
	B	64317	643 017 085	143	850	508	216	201	224	3	A	34..5
		65017	650 017 085	150	850	508	216	201	224	3	A	35.8
		66514	665 014 095	165	950	508	216	201	224	3	A	36.5
		67043	670 043 100	170	1000	508	216	201	224	3	A	38.5
		68032	680 032 100	180	1000	508	216	201	224	3	A	40
	C	70027	700 027 105	200	1050	509	264	217	237	3	A	45.5
		70029	700 029 105	200	1050	509	264	217	237	4	A	45.5
71014		710 014 115	210	1150	509	264	217	237	3	A	46.4	
73011		730 011 120	230	1200	509	264	217	237	3	A	48.1	
JIS	F51	115F51	N120	120	640	504	180	211	232	4	A	30.6
		150F51	N135	135	720	504	180	211	232	4	A	31.5
		145F51	N140	140	780	504	180	211	232	4	A	33
	G51	145G51	N150	150	950	507	220	213	234	4	A	35.6
		165G51	N160	160	950	507	220	213	234	4	A	36.5
		180G51	N170	170	950	507	220	213	234	4	A	38.5
		195G51	N180	180	1000	507	220	213	234	4	A	40
	H52	210H52	N200	200	1200	512	265	216	240	4	A	45.5
245H52		N220	220	1300	512	265	216	240	4	A	48.1	
BCI	4D	4D-950		150	950	507	220	213	234	4	A	35.6
	8D	8D-1300		200	1300	509	264	217	237	4	A	48.1

