



Notes:

1. Raceway of inner & outer ring induction hardened. hardness: 55~62HRC
Depth ≥ 3.0mm
2. Inner & outer ring quenched & tempered, hardness: 207~262HB

Gear Data				Design	Check			Model	QNA.560.20A		Weight	77kg	
Module	m	5	Gear heat treatment requirements HRC	Date	Approve				Name	Slewing Bearing	Qty	Scale	
Teeth no	z	88		Inner ring mounting hole	Qty	Size	Axial clearance		0.04~0.25	Material	50Mn	Total 1 page	The 1st page
Teeth pressure angle	α	20°	Precision(GB10095-88)	10	Outer ring mounting hole	14	Φ18	Radial clearance	0.04~0.25	Machine tolerances without notes			
Modification coefficients	x	+0.5			Oil hole	2	M8×1			≤200	≤500	≤710	≤1120
Reduction coefficients	km	0								±0.30	±0.40	±0.50	±0.65
Pitch diameter	d	440								≤1600	≤2000	≤2500	≤3150
										±0.80	±0.95	±1.10	±1.35
										≤4000	≤5000		
										±1.65	±2.0		
										Technical processing standards without notes according to ...JB/T2300-2011			
				T:Pulg location S:Soft zone Y:Oil hole Z:Lifting hole				<p style="text-align: center;">XUZHOU WANDA SLEWING BEARING CO.,LTD</p> <p>Fax: +86 516 83309366 Fax: +86 516 83915766 http://www.slew-bearing.com</p>					