



Bench-Top Temperature & Humidity Chamber



Energy Conservation




Remote network system



Circuit System



Optimal space use with stand options



● Specifications

Model		SMC-22-CC
Temperature	Temperature range	-60℃~180℃ (A:0℃~180℃;B: -20℃~180℃; C: -40℃~180℃;D:-60℃~180℃)
	Temperature fluctuation	±0.5℃
	Cooling rate	180.0℃~-60.0℃ Within about 100 minutes 1.0~3.0℃/min
	Heating rate	-60.0℃~180.0℃ Within about 60 minutes 3.0~5.0℃/min
	Temperature uniformity	±1.0℃ (-40.0℃~100.0℃) ±1.5℃ (100.1℃~180.0℃or-40.0℃~-60.0℃)
Humidity	Humidity range	20.0%RH~98.0%RH
	Humidity fluctuation	±1.0% RH
	Humidity uniformity	±2.0%RH
Material	Internal material	SUS304 stainless steel(1.2mm)
	External material	cold-rolled plate(1.2mm),powder coating
	Heat insulation	poly urethane foam(100mm)+glass wool(10mm)
	Fan	Centrifugal fan(Impeller Fan)
	Refrigeration compressor	hermetic compressor(Tecumseh)
	Cooling mode	SANWOOD air cooling
	Refrigerant	R404A、R23、R508
	Evaporator	finned-tube exchanger
	Heater	nickel chrome strip heater
Size	Humidifier	Steam Humidifier
	Interior(mm) W*H*D	300 X 300 X 250 22.5L
	Exterior(mm) W*H*D	500X850X1150
	Weight	85kg
Working Temperature		+5 ~ 35℃
Power supply		220V/AC 50/60Hz 12A
Controller		Standard: South Korea TEMI-1500 Optional: South Korea TEMI-2500,South Korea TEMI-2700

Sanwood (HK) Industrial Corporation.,limited
Guangdong Sanwood Technology Corporation.,limited

ADD: No.88, Songchang Road, Songbotang , Changping, Dongguan, Guangdong
TEL: +86+769-81182799
FAX: +86+769-82987199
E-mail: info@sanwood.cc
www.sanwood.cc
www.climatic-chambers.com



Mobile phone scan
can visit our official website